

**HARDOX®**  
WEAR PLATE

# INTRODUCING THE NEW GENERATION HARDOX® WEAR PLATE



# THE BEAST HAS DONE IT AGAIN

**Hardox® 500 Tuf is the latest upgrade in the Hardox® range. It delivers high strength, extreme hardness and guaranteed toughness in one and the same wear plate.**

Hardox® 500 Tuf combines the best properties from the Hardox® 450 and Hardox® 500 grades. The result is a wear plate with no real competition on the market.

It has the toughness necessary to perform as a structural material in heavy-duty tipper bodies, containers and buckets. It also works in freezing conditions as the impact energy values indicate.

Superior wear and dent resistance gives extended service life and the ability to endure heavy impact.

Typical working conditions include loading and unloading of heavy and sharp rocks in quarries and mines, handling large and heavy steel scrap, and in demolition when pieces of concrete with rebar are loaded or dropped into tipper.

Hardox® 500 Tuf has a guaranteed impact energy of 27 J at -20°C, and a typical value of 45 J at -40°C. It has an unusually narrow Brinell hardness window of 475-505 HBW. The estimated relative service life for Hardox® 500 Tuf is 85-100% longer than for Hardox 400® according to WearCalc and TippCalc.\*

**WORKSHOP-FRIENDLY**

Hardox® 500 Tuf can be processed by the same kind of machinery used for other Hardox® grades. Bendability recommendations are similar to those for Hardox® 450.

Hardox® 500 Tuf																						
Hardness nominal HBW		Impact toughness CVT guaranteed J at -20°C (ft-lb at -4°F)		Impact toughness CVL typical for 20 mm (¾"), J at -40°C (ft-lb at -40°F)		Relative service life interval (relative to Hardox® 400)		CEV/CET typical for 20 mm (¾")		Thickness range mm (inches)												
475-505		27 J (20 ft-lb)		45 J (33 ft-lb)		1.3-2.1		0.52/0.36		4-25 mm (5/32"-0.985")												
Width	1000-	1351-	1500-	1601-	1701-	1801-	1901-	2001-	2101-	2201-	2301-	2401-	2501-	2601-	2701-	2801-	2901-	3001-	3101-	3201-	3301-	
Thickness	1350	1499	1600	1700	1800	1900	2000	2100	2200	2300	2400	2500	2600	2700	2800	2900	3000	3100	3200	3300	3350	
3.0-3.7																						
3.8-4.7																						
4.8-5.7																						
5.8-6.7																						
6.8-7.7																						
7.8-8.7																						
8.8-10.0																						
10.1-24.0																						
24.1-25.0																						

■ Some restrictions, contact your local sales representative for information   ■ Outside the range of dimensions

\*The calculations are based on sliding wear with granite.

